

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
24 January 2002 (24.01.2002)


PCT

(10) International Publication Number
WO 02/06135 A1

- (51) International Patent Classification⁷: **B65D 83/04**, 55/02, 43/12 // 101:00
- (21) International Application Number: PCT/AU01/00844
- (22) International Filing Date: 13 July 2001 (13.07.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: PQ 8762 14 July 2000 (14.07.2000) AU
- (71) Applicant (for all designated States except US): **WESTERN RESEARCH & DEVELOPMENT LIMITED** [AU/AU]; Unit 4, 50 Achievement Way, Wangara, W.A. 6065 (AU).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **McHUTCHISON, Roy, Neil** [AU/AU]; 76 Douglas Avenue, South Perth, W.A. 6151 (AU).
- (74) Agent: **WATERMARK PATENT & TRADEMARK ATTORNEYS**; Level 21, Allendale Square, 77 St Georges Terrace, Perth, W.A. 6000 (AU).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: TAMPER PROOF SLIDE COVER CONTAINER



(57) Abstract: A tamper proof container comprising: a container body (1) within which product can be accommodated, the container body having an access opening (7); a cover (9) separable from the container body for closing the access opening and including engagement means (37, 43) for engaging the container body when over the access opening; and tamper prevention means (11) for preventing removal of the cover when located over the access opening, the tamper prevention means including at least one locking element (15); wherein the locking element(s) is adapted to allow an initial engagement of the cover to the container body over the access opening while preventing subsequent removal therefrom; and wherein the locking element(s) is separable from the container, the separation of the locking element(s) allowing the removal of the cover from the container body, the removal of the locking element(s) further providing a visual indication that the container has been opened.

WO 02/06135 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

TAMPER PROOF SLIDE COVER CONTAINER

The present invention is generally directed to containers for storing products, and in particular to a container having tamper prevention features. Although the present invention will be described with respect to the packaging of
5 medical or hygiene products such as drug capsules or tablets, condoms or tampons and band aids, it is to be appreciated that the present invention is not restricted to this application and that other uses are also envisaged.

Products of the above mentioned type are commonly sold in cardboard cartons. These cartons can be covered by heat wrapped plastic sheeting to
10 afford a limited degree of tamper prevention by preventing the opening of the carton to gain access to the contents without tearing of the plastic wrapping. The tearing of the wrapping provides a visual indication that the packaging has been opened. This type of wrapping does not however prevent a more malicious form of tampering where the products are dosed with foreign substances such as
15 poison by using a syringe needle. The hole produced by the needle can be located to escape notice so that the tampering of the product remains undetected.

Although such malicious tampering could be overcome by enclosing the product in a heat welded hard plastic casing, it has until now been uneconomical to do so as it would add significantly to the overall selling cost of the product.
20 Also, such a hard casing could well be difficult to open by the final end user of the product.

It is therefore an object of the present invention to provide a tamper proof container for protecting any product stored within from the type of malicious tampering referred to above.

25 It is another object of the present invention to provide a tamper proof container that provides a visual indication of the container having been opened.

It is a further object of the present invention to provide a tamper proof container that is relatively economical to manufacture, and is also relatively easy to open by the end user.

30 With this in mind, according to the present invention, there is provided a tamper proof container comprising:

a container body within which product can be accommodated, the container body having an access opening;

a cover separable from the container body for closing the access opening and including engagement means for engaging the container body when over the access opening; and

5 tamper prevention means for preventing removal of the cover when located over the access opening, the tamper prevention means including at least one locking element;

 wherein the locking element(s) is adapted to allow an initial engagement of the cover to the container body over the access opening while preventing subsequent removal therefrom;

10 and wherein the locking element(s) is separable from the container, the separation of the locking element(s) allowing the removal of the cover from the container body, the removal of the locking element(s) further providing a visual indication that the container has been opened.

 A tamper proof container according to the present invention can be filled
15 with product through the access opening, the cover being subsequently installed over the access opening and prevented from subsequent removal by the tamper prevention means. It is however also envisaged that the tamper proof container could be filled with product during assembly of the container.

 The access opening may be provided in a wall(s) of the container body,
20 and the engagement means of the cover may provide a releasable engagement of the cover to the container body when located over the access opening. The cover may be at least substantially flush with the wall(s) when engaged with the container body. This provides a relatively smooth profile for the container when closed giving it a visually pleasing appearance.

25 According to a first preferred embodiment of the present invention, the cover may be in the form of a slide cover slidably supportable over the access opening. The slide cover may include a peripheral lip extending along at least a portion of the periphery thereof. The peripheral lip may be adapted to engage a cooperating shoulder or channel in the container body located adjacent to the
30 access opening to allow sliding motion of the slide cover relative to the access opening. The engagement means for the slide cover may include one or more tungs located at one end of the slide cover, the or each tung respectively engaging a cooperating lug on the container body. This lug may be provided on

an internal surface of the container body adjacent the access opening. The engagement means of the slide cover may also include one or more lugs and one or more cooperating apertures respectively provided on an inner face of the peripheral lip of the cover at an opposing end of the slide cover to the tung(s) or in the container body adjacent the access opening, the lug(s) being accommodated within the aperture when the slide cover completely closes the access opening. The cooperating tung(s) and lug(s) on one end of the cover acts to hold that end of the slide cover in position, and the cooperating lug(s) and aperture(s) on the other end of the slide cover acts to prevent the lifting of that end away from the access opening. It should be appreciated that other engagement means for the slide cover are also envisaged. The use of a cover having a peripheral lip engaging a cooperating shoulder ensures that there is no ready access for a hypodermic syringe at the junction between the cover and the container body.

The locking element of the tamper prevention means may include a locking tab extending from the container body adjacent the access opening. The locking tab may extend at least substantially perpendicular relative to the plane of the access opening thereby preventing separation of the slide cover from the container body. The locking tab may be attached to the rest of the container body by a frangible connection portion thereof. The locking tab may be integrally formed with the container body with a relatively thin wall section between the locking tab and the rest of the container wall to provide the frangible connection portion for the locking tab. The locking tab may include a contact face located on a side of the locking tab facing the access opening. The contact face may be inclined at an acute angle relative to the plane of the access opening. The purpose of the inclined face will be subsequently described. A hanging hook or web having a hanging hole may also extend from the locking tab.

According to the second preferred embodiment of the present invention, the engagement means for the cover may include a peripheral rib extending along at least a portion of the periphery of the cover, the peripheral rib being locatable within a cooperating groove in the container body. This arrangement helps to make it even more difficult to insert a needle between the cover and the container body while at the same time helping to hold the cover in position over the access opening.

The engagement means of the cover may further include one or more tags extending from an inner face of the cover, said tag(s) forming part of a coupling arrangement for engaging the cover to the container body. An aperture may be provided in the tag(s) for engaging a cooperating lug provided within the container
5 body as another part of the coupling arrangement. The lug(s) may be resiliently biased and supported on a manual actuator mechanism for allowing the release of the lug(s) from the cooperating tag(s) thereby allowing the removal of the cover from the container body. The lug(s) may be mounted on a part of the manual actuator mechanism. The manual actuator mechanism may include a biased
10 latch, whereby movement of the latch disengages the coupling arrangement.

The locking element of the tamper prevention means may be provided on the cover, the locking element preventing movement of the latch thereby preventing the release of the cover from the container body. The locking element may include a locking tab located immediately adjacent the latch, the locking tab
15 being connected to the cover by a frangible connection. The locking tab may be integrally formed with the cover with a relatively thin wall section between the locking tab and the rest of the cover to provide a frangible connection portion for the locking tab.

The container body may be of any shape depending on the type of product
20 to be accommodated. For example, the container body may be rectangular or square in shape when seen in plan view and may having a relatively narrow profile when seen from the side. Such a container body would be appropriate for flat products such as blister packed tablets or capsules or flat packed condoms. Other container shapes are however envisaged. For example, the container
25 could also be round, or a pentagon or hexagon shape when seen in plan view.

The container body may be manufactured in two or more sections and subsequently assembled. To this end, each section may include cooperating coupling means to facilitate this assembly. According to an example arrangement
30 according to the present invention, the container body may be made of two separate casing shells. A series of female snap tungs may be provided along the peripheral edge of one casing shell, and a series of cooperating male lugs may be provided adjacent the peripheral edge of the other casing shell to enable a "snap clip" non-removal connection between the casing shells. The two casing shells

can then be assembled by bringing the two casing shells together such that the female tungs and male lugs are engaged. A rib may be provided along the peripheral edge of one of the casing shells, and a cooperating shoulder or channel may be provided along the peripheral edge of the other casing shell.

- 5 When the two casing shells are brought together, the rib can be accommodated by the shoulder or rib. This prevents the ready access of a hypodermic needle at the junction between the two casing shells.

The container body and cover should be made of a material that is relatively rigid. This helps to prevent gaps being formed at the junction between
10 the sections of the container body and/or the cover and the container body due to deformation of the container body by pressure being applied thereon. The material should also enable the locking tab to be separated from and the container body at the frangible connection thereof. Suitable material include relatively rigid material such as ABS plastic.

- 15 It is also envisaged that the container body sections could alternatively be ultrasonically welded or glued together to eliminate any junctions. It is however general preferable to use a joining arrangement as described above as this can facilitate automatic assembly of the container reducing the production time and costs of the container.

- 20 The locking tab in the first preferred embodiment according to the present invention operates in the following manner.

The slide cover can be initially fitted to the container body when the locking tab is in position. The slide cover is initially engaged by the tung(s) at one end of the slide cover to the container body over the access opening, with the slide cover
25 being positioned at an angle to the plane of the access opening. The other end of the slide cover will initially abut against the inclined face of the locking tab. The frangible connection portion of the locking tab is sufficiently resilient to allow for some deflection of the locking tab. The slide cover can therefore be displaced towards the access opening in a pivotal movement about the engaged end of the
30 slide cover, the other end abutting the inclined face of the locking tab. The pivotal displacement of the slide cover applies a force on the locking tab resulting in deflection thereof. When the slide cover is in position over the access opening, the other end of the slide cover adjacent the locking tab engages the container

body. The locking tab returns to its initial position and blocks any sliding motion of the slide cover that would be required to release the engagement means of the cover and allow the cover to be removed from the container. Any attempt to slide open and remove the slide cover would result in the breaking of the locking tab from the container body.

5 The end user of the container can gain access to the product stored therein by breaking off the locking tab and sliding open the slide cover to opening the access opening of the container body. The absence of the locking tab provides a clear indication that the container has been opened. Having the
10 hanging hook located on the lock tab which is removed together with that lock tab also helps to provide this visual indication. The slide cover can then operate in the usual manner to close the container for storing the remaining contents therein.

In the above described arrangement, the locking element is removed by a pivot break where the locking element is pivoted about its frangible connection. It
15 is however also envisaged that the arrangement of the container is such that the locking element is broken with a twist or circular break, for example when two sections of the container can pivotally slide relative to each other to open the container.

The locking tab in the second embodiment according to the present
20 invention operates in the following manner.

An opening may be provided in the cover through which the latch of the manual actuator mechanism can be located. The locking tab may be located and form one side of the opening. The cover may be located in a position over the access opening, with the tagss of the cover engaging the cooperating lugs of the
25 manual actuator mechanism. The cover is therefore located in position over the access opening. The bias of the lugs allow the lugs to engage cooperating apertures of the tags. The location of the locking tab however prevents movement of the latch preventing the release of the cover from the container body.

30 The locking tab must therefore be separated from the rest of the cover before the latch can be moved to release the cover from the container body. The removal of the locking tab provides a visual indication of any tampering of the

container. Following the opening of the container, the cover can be retained in position on the container by the manual actuator mechanism.

5 The tamper proof container according to the present invention is resistant to tampering by the use of hypodermic syringes and cannot be opened without providing a clear visual indication that the container has been opened. The container can however continue to be used as a storage container after opening, with the cover still having engagement means for engaging the cover over the access opening.

10 It will be convenient to further describe the invention with respect to the accompanying drawings, which illustrate a preferred embodiment of the tamper proof container according to the present invention. Other preferred embodiments of the invention are possible, and consequently, the particularity of the accompanying drawings is not to be understood as superceding the generality of the preceding description of the invention.

15 In the drawings:

Figure 1 is an isometric view of a first preferred embodiment of a tamper proof container according to the present invention;

Figure 2 is a plan view of the tamper proof container of Figure 1;

20 Figure 3 is a cross sectional view of the tamper proof container of Figure 1 taken along line A-A in Figure 2;

Figure 4 is an isometric view of a first half casing of the tamper proof container of Figure 1;

Figure 5 is an isometric view of a second half casing of the tamper proof container of Figure 1;

25 Figure 6 is an isometric view of a slide cover of the tamper proof container of Figure 1;

Figures 7 and 8 are detailed cross sectional view showing the engagement of the slide cover to the container body of the tamper proof container of Figure 1;

30 Figure 9 is a detailed isometric view of the tamper prevention means of the tamper proof container of Figure 1;

Figure 10 is an isometric view of the opposing side of the tamper protection means of Figure 9;

Figure 11 is a detailed cross sectional view of the tamper prevention means of Figure 9 and 10;

Figure 12 is a detailed view of the snap connection of the first and second half casings as shown in Figure 4 and 5;

5 Figure 13 are respective isometric views showing the sequence of operation of the tamper proof container as shown in Figure 1;

Figure 14 is an isometric view of a second preferred embodiment of a tamper proof container according to the present invention;

Figure 15 is a side view of the tamper proof container of Figure 14;

10 Figure 16 is a plan view of the tamper proof container of Figure 14;

Figure 17 is a plan view of the tamper proof container of Figure 14 showing section line B-B;

Figure 18 is a detailed cross-sectional view showing the engagement of the slide cover to the container body of the tamper proof container of Figure 14;

15 Figure 19 is a cross-sectional view taken along line B-B of Figure 17;

Figure 20 is a detailed cross-sectional view of the tamper protection means of the tamper proof container of Figure 14;

Figure 21 is a partially exploded isometric view of the tamper proof container of Figure 14;

20 Figure 22 is a plan view of the tamper proof container of Figure 14 showing section lines C-C and D-D;

Figure 23 is a cross-sectional view of the tamper proof container of Figure 22 taken along line C-C;

25 Figure 24 is a cross-sectional view of the tamper proof container of Figure 22 taken along line D-D;

Figures 25 to 30 are respective isometric views showing the sequence of operation of the tamper proof container as shown in Figure 14;

Figure 31 is an isometric view of a third preferred embodiment of a tamper proof container according to the present invention;

30 Figure 32 is a side view of the tamper proof container of Figure 31;

Figure 33 is a plan view of the tamper proof container of Figure 31;

Figure 34 is a plan view of the tamper proof container of Figure 31 showing section line E-E;

Figure 35 is a cross-sectional view of the tamper proof container of Figure 34 taken along line E-E;

Figure 36 is a plan view of the tamper proof container of Figure 31 showing section lines F-F, G-G, H-H, I-I, and J-J;

5 Figure 37 is a cross-sectional view of the tamper proof container of Figure 36 taken along line F-F;

Figure 38 is a cross-sectional view of the tamper proof container of Figure 36 taken along line G-G;

10 Figure 39 is a cross-sectional view of the tamper proof container of Figure 36 taken along line H-H;

Figure 40 is a cross-sectional view of the tamper proof container of Figure 36 taken along line I-I;

Figures 41 to 46 are detailed cross-sectional views showing the operation of the tamper prevention means of the tamper proof container of Figure 31;

15 Figure 47 is a detailed cross-sectional view showing the manual actuator mechanism of the tamper proof container of Figure 31;

Figure 48 is a further cross-sectional view of the tamper proof container of Figure 31; and

20 Figure 49 is an isometric cross-sectional view of the tamper proof container of Figure 31 showing a tablet sheet located therein.

Corresponding features in each of the preferred embodiments of a tamper proof container according to the present invention have been designated with the same reference numeral for clarity reasons.

Referring initially to Figures 1 to 5, there is shown a first preferred
25 embodiment of a tamper proof container according the present invention including a container body 1 formed from a first half casing 3 and a second half casing 5. The first half casing 3 includes an access opening 7 for the container body 1. This access opening 7 is closed off by a cover 9, and the tamper proof container further includes tamper prevention means 11 including a locking element 15. A
30 product hanging tag 17 is secured to and forms part of the locking element 15. The first half casing 3 and second half casing 5 are held together by means of a snap connection 19 therebetween as shown in Figure 3. This snap connection 19 comprises a series of female snap tungs 21 provided along a peripheral edge 4 of

the first half casing 3. The snap connection 19 also includes a series of male lugs 23 provided along a peripheral edge 6 of the second half casing 5. When the first and second half casings 3, 5 are brought together, the female snap tungs 21 are deflected over an inclined face 24 of the cooperating male lug 23 until the lug 23 is accommodated within an aperture 22 provided in the female snap tung 21 as best shown in Figure 12. The peripheral edge 4 of the first half casing 3 includes a groove 27 adjacent each female snap tung 21 or a shoulder 29 at portions of the peripheral edge 6 away from the female snap tungs 21. This groove 27 or shoulder 29 accommodates a rib 31 provided along the peripheral edge 6 of the second half casing 5, as shown in Figures 11 and 12. This cooperation between the first half casing peripheral edge 4 and the second half casing peripheral edge 6 helps to prevent the access of a hypodermic syringe through the join line 2 between the half casings.

Figure 6 shows in more detail the features of the slide cover 9 of the tamper proof container. Figure 6 shows the interior surface of the slide cover 9 which includes a peripheral lip 35 extending along all except one side of the slide cover 9. The retaining side of the slide cover includes an engagement tung 37 for engaging the container body 1. The peripheral lip 35 rests on a shoulder 36 provided about the access opening 7 in the first half casing 3. The retaining side of the slide cover 9 further includes a flange 39 which rests upon a shoulder 41 provided on one end of the access opening 7 of the first half casing 3. The other end of the slide cover 9 opposite to the engagement tung 37 includes two male lugs 43 for engaging cooperating apertures 45 provided on the first half casing 3 adjacent the access opening 7 on either side of the locking element 15.

Figures 7 and 8 show how the cover 9 engages the first half casing 3 immediately adjacent the access opening 7. A cooperating lug 45 is provided on an interior surface of the first half casing 3 adjacent the access opening 7. A finger depression 47 is provided on the cover 9 adjacent to the engagement tung 37.

The cooperation of the engagement tung 37 and the cooperating lug 45 serves two functions. Firstly, they provide a pivot point about which the slide cover 9 can rotate when it is initially installed on to the container body 1 over the access opening 7. Secondly, they act to retain the slide cover 9 over the access

opening 7. The slide cover 9 is further retained over the access opening 7 by the cooperation of the lugs 43 with the apertures 45 at the opposing end of the cover 9.

5 Figures 9 to 11 more clearly show the tamper prevention means 11 of the present invention. The locking element 15 of the tamper prevention means 11 is secured to the second half casing 5 by a frangible connection 51. The locking element 15 further includes an inclined inner surface 53 which is adapted to the located in a closely adjacent or abutting relationship with the peripheral lip 35 of the slide cover 9.

10 The cover 9 is initially installed over the access opening 7 with the locking element 15 in position. This is achieved by initially securing the engagement tung 37 of the slide cover 9 to the cooperating lug 45, with the slide cover 9 located at an angle away from the plane of the access opening 7. The peripheral lip 35 of the slide cover 9 rests against the inclined face 53 of the locking element 15. The
15 frangible connection 51 provides a sufficient resilience to allow a slight deflection of the locking element 15 such that the peripheral lip 35 of the slide cover 9 can slide over the inclined face 53 down towards the final closed position of the slide cover 9. When the slide cover 9 is in that position, the male lugs 43 engage the cooperating apertures 45 on the first half casing 3 and the locking element 15
20 returns to its initial position. The slide cover 9 can only be removed from the container body 1 by moving it in a sliding motion parallel to the plane of the access opening 7. This is however not possible because the locking element 15 is blocking this motion. The only way that the cover 9 can be removed is therefore by removal of the locking element 15.

25 Figure 13 shows in more detail the operation sequence of the tamper proof container. Moving from right to left in Figure 13, the person opening the container can use their finger 16 to apply a force on the locking element 15. Because the locking element 15 is secured by a frangible connection 51 to the second half casing 5, the locking element 15 and associated product hanging tag 17 can be
30 broken off the rest of the container body 1. The removal of the locking element 15 then allows for the opening of the slide cover 9 with the person applying finger pressure to the finger depression 47 of the cover 9 to release the engagement tung 37 from the cooperating lug 45 and subsequently sliding the slide cover 9 in

a direction parallel to the plane of the access opening 7 to open said access opening.

The product tag 17 is used to hang the container within a shop display. Therefore, the removal of the locking element 15 and associated support tag 17 provides a clear visual indication of the tampering or opening of the container. Furthermore, the container body is produced using relatively rigid thermoplastic such as ABS or related thermoplastic materials. This means that the snap connection 19 interconnecting the first and second half casings 3, 5 cannot be separated by the application of opposing forces on either side of the container body 1. This prevents any gap being formed at the junction 2 by the application of this force. This interaction, together with the cooperation of the first half casing peripheral edge 4 and the second half casing peripheral edge 6 as shown in Figures 11 and 12 ensure that it is not possible to gain access to the contents of the container using a hypodermic needle through the junction 2. The plastic is also of sufficient density to prevent the hypodermic needle penetrating through any of the walls of the container body or slide cover 9.

Figures 14 to 30 shows a second preferred embodiment of a tamper proof container according to the present invention. The principle of operation of this second preferred embodiment is identical to that of the first preferred embodiment as shown in Figures 1 to 13. The second embodiment is however specifically adapted for tablet sheets of the type used to package drug capsules or tablets.

Referring initially to Figures 14 to 16, the second preferred embodiment of the tamper proof container has a flatter and thinner profile than the first preferred embodiment shown in Figures 1 to 13. However, as shown in Figures 17 to 30, the operation of the second preferred embodiment of the tamper proof container according to the present invention operates in an identical fashion with the cover 9 being held in position by a locking tab 15. Removal of the locking tab 15 as shown in the sequence of Figures 25 to 30 allows for the separation of the cover 9 from the container body 1 thereby allowing access into the contents of the tamper proof container shown as tablet sheets 58.

Figures 31 to 49 show a third preferred embodiment of a tamper proof container according to the present invention. This tamper proof container is similar in shape to that of the second embodiment shown in Figures 14 to 30.

The tamper prevention means and the cover engagement means for engaging the cover 9 to the container body 1 is however somewhat different.

Figures 31 to 33 show that the third preferred embodiment of the container has a similar flat profile to the second embodiment. However, unlike the preceding embodiments, the engagement means for the cover 9 is provided by a manual actuator mechanism 60. Furthermore, the tamper prevention means is provided by a locking tab 62 which forms part of the cover 9.

Figures 34 to 49 show in more detail the operation of both the manual actuator mechanism 60 and the locking tab 62 of the tamper prevention means. The manual actuator mechanism includes a latch 64 that extends through an opening 66 provided in the cover 9 (best shown in Figure 48). The manual actuator mechanism 60 further includes a pair of resilient supports 68 (best shown in Figures 47 and 48). The resilient support 68 provides a biasing for the latch 64. The manual actuator mechanism 60 further includes a number of lugs 70 which engage apertures 72 provided in respective tags 71 extending from an interior face of the cover 9. When the cover is located over the access opening of the container body 1, the lugs 70 engage the apertures 72 of the cover 9 thereby holding the cover in position on the container body 1. The resilient supports 68 act to urge the lugs 70 into engagement with the cooperating apertures 72 of the cover 9.

The locking tabs 62 is integrally formed with the cover 9 and is located and forms one side of the opening 66 through which the latch 64 extends. The locking tab 62 is connected by a thin wall section frangible portion 63 to the rest of the cover 9.

As best shown in figures 48 and 49, the cover 9 includes a peripheral rib 77 extending along the periphery of the cover 9. This peripheral rib 77 engages a cooperating groove 75 provided in the container body 1, therefore when the cover 9 is located over the access opening of the container body 1, the peripheral rib 77 of the cover 9 is located in the cooperating groove 75 of the container body. This arrangement further assists in locating the cover 9 on the container body 1 while further restricting the access of any needle into the container through the join line between the container body 1 and the cover 9.

Figures 41 to 46 show the sequence of operation of the tamper prevention means. As shown in Figure 42, the locking tab 62 can be separated from the rest of the cover 9. This therefore frees the latch 64 for movement as shown in Figure 43. The movement of the latch 64 releases the lugs 70 from the cooperating apertures 72 of the cover. The cover 9 can then be separated from the rest of the container body as sequentially shown in Figures 44 to 46.

The separation of the locking tab 62 from the cover 9 would provide an indication of the possibility of the tampering of the contents of the tamper proof container. After the locking tab 62 has been removed from the cover 9, the manual actuator mechanism 60 can still act to securely retain the cover 9 on the container body 1. The cover 9 can be simply removed by displacement of the latch 64 as previously described.

Modifications and variations as would be deemed obvious to the person skilled in the art are included within the ambit of the present invention as defined in the appended claims.

Claims:

1. A tamper proof container comprising:
 - a container body within which product can be accommodated, the container body having an access opening;
 - a cover separable from the container body for closing the access opening and including engagement means for engaging the container body when over the access opening; and
 - tamper prevention means for preventing removal of the cover when located over the access opening, the tamper prevention means including at least one locking element;
 - wherein the locking element(s) is adapted to allow an initial engagement of the cover to the container body over the access opening while preventing subsequent removal therefrom;
 - and wherein the locking element(s) is separable from the container, the separation of the locking element(s) allowing the removal of the cover from the container body, the removal of the locking element(s) further providing a visual indication that the container has been opened.
2. A tamper proof container according to claim 1, wherein the access opening is provided in a wall(s) of the container body, and the engagement means of the cover provides a releasable engagement of the cover to the container body when located over the access opening, the cover being at least substantially flush with the wall(s) when engaged with the container body.
3. A tamper proof container according to claim 2, wherein the includes a peripheral lip extending along at least a portion of the periphery thereof, the peripheral lip being adapted to engage a cooperating shoulder in the container body located adjacent to the access opening.
4. A tamper proof container according to claim 3, wherein the cover is in the form of a slide cover slidably supportable over the access opening, the engagement of the peripheral lip of the slide cover on the cooperating shoulder of the container body allowing slide motion of the slide cover relative to the access

opening, the engagement means for the slide cover including one or more tungs located at one end of the slide cover, the or each tung respectively engaging a cooperating lug on the container body, the or each said lug being provided on an internal surface of the container body adjacent the access opening.

5. A tamper proof container according to claim 4, wherein the engagement means of the container slide cover further includes one or more lugs and one or more cooperating apertures respectively provided on an inner face of the peripheral lip of the cover at an opposing end of the slide cover to the tung(s) or in the container body adjacent the access opening, the lug(s) being accommodated within the aperture when the slide cover completely closes the access opening.

6. A tamper proof container according to claim 5, wherein the locking element of the tamper prevention means includes a locking tab extending from the container body adjacent the access opening, the locking tab extending at least substantially perpendicular relative to the plane of the access opening to thereby block the movement of the slide cover thereby preventing separation of the slide cover from the container body.

7. A tamper proof container according to claim 6, wherein the locking tab is attached to the rest of the container body by a frangible connection portion thereof.

8. A tamper proof container according to claim 7, wherein the locking tab is integrally formed with the container body with a relatively thin wall section between the locking tab and the rest of the container wall to provide the frangible connection portion for the locking tab.

9. A tamper proof container according to claim 8, wherein the locking tab includes a contact face located on a side of the locking tab facing the access opening, the contact face being inclined at an acute angle relative to the plane of the access opening.

10. A tamper proof container according to any one of claims 7 to 10, wherein a means for hanging the container extends from the locking tab.

11. A tamper proof container according to claim 3, wherein the engagement means for the cover includes a peripheral rib extending along at least a portion of the periphery of the cover, the peripheral rib being locatable within a cooperating groove in the container body.

12. A tamper proof container according to claim 11, wherein the engagement means of the cover further includes one or more tags extending from an inner face of the cover, said tag(s) forming part of a coupling arrangement for engaging the cover to the container body.

13. A tamper proof container according to claim 12, wherein the coupling arrangement includes an aperture provided in the tag(s) for engaging a cooperating lug provided within the container body.

14. A tamper proof container according to claim 13, wherein the lug(s) are resiliently biased and supported on a manual actuator mechanism for allowing the release of the lug(s) from the cooperating tag thereby allowing the removal of the cover from the container body.

15. A tamper proof container according to claim 13 or 14, the manual actuator mechanism including a biased latch, whereby movement of the latch disengages the coupling arrangement.

16. A tamper proof container according to claim 15, wherein the locking element of the tamper prevention means is provided on the cover, the locking element preventing movement of the latch thereby preventing the release of the cover from the container body.

17. A tamper proof container according to claim 16, wherein the locking element includes a locking tab located immediately adjacent the latch, the locking


tab being connected to the cover by a frangible connection.

18. A tamper proof container according to claim 17, wherein the locking tab is integrally formed with the cover with a relatively thin wall section between the locking tab and the rest of the cover to provide a frangible connection portion for the locking tab.

19. A tamper proof container according to any one of the preceding claims, wherein the container body is made of two casing shells, a series of female snap tungs being provided along the peripheral edge of one casing shell, and a series of cooperating male lugs being provided adjacent the peripheral edge of the other casing shell to enable an interconnection between the casing shells.

20. A tamper proof container according to claim 19, wherein a rib is provided along the peripheral edge of one of the casing shells, and a cooperating shoulder or channel is provided along the peripheral edge of the other casing shell, wherein when the two casing shells are brought together, the rib can be accommodated by the shoulder or rib.

1/22






FIG 3
SECTION A - A





FIG 4








FIG 6

6/22



7/22





FIG 9



9/22




FIG 12

FIG 11




FIG 13




FIG 14




FIG 15




FIG 16

12/22




FIG 17




FIG 18








FIG 19

13/22






14/22





16/22



17/22




FIG 34




FIG 35
SECTION E - E

18/22




FIG 37
SECTION F - F




FIG 38
SECTION G - G




FIG 39
SECTION H - H











FIG 40
SECTION I - I



19/22



20/22






FIG 47



21/22

FIG 4B



INTERNATIONAL SEARCH REPORT

International application No.
PCT/AU01/00844

A. CLASSIFICATION OF SUBJECT MATTER

Int. Cl. ⁷: B65D 83/04, 55/02, 43/12 // B65D 101:00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

Refer Electronic data base consulted below

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

DWPI IPC A61J 1/-, 3/-, 7/-, A45C 11/-, A47G 29/-, B65D 17/-, 43/-, 50/-, 51/-, 77/30, 83/04, 101/00
& keywords: TAMPER, FRANGIBLE, SEPARABLE, TAB, COVER and similar terms

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4787526 A (PEHR) 29 November 1988 Column 11 lines 1-27 & See figures 31, 32	1-3, 11
X	WO 90/14999 A (AKERLUND & RAUSING LICENS AB) 13 December 1990 See whole document	1-3, 11
A	US 5878887 A (PARKER et al.) 9 March 1999 See whole document	

☒ Further documents are listed in the continuation of Box C ☒ See patent family annex

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier application or patent but published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

Date of mailing of the international search report
- 5 NOV 2001

Name and mailing address of the ISA/AU

AUSTRALIAN PATENT OFFICE
PO BOX 200, WODEN ACT 2606, AUSTRALIA
E-mail address: pct@ipaustalia.gov.au
Facsimile No. (02) 6285 3929

Authorized officer

DEREK BUTLER

Telephone No : (02) 6283 2347

INTERNATIONAL SEARCH REPORT

International application No.
PCT/AU01/00844

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2219284 A (DRG (UK) LIMITED) 6 December 1989 See whole document	

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.
PCT/AU01/00844

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report			Patent Family Member			
US	4787526	AU	32806/89	CA	1316844	EP 401292
		WO	8908057	US	4925041	US 5013073
		US	5137260	US	4809874	US 4898073
		DE	3740691	EP	318681	
WO	9014999	AU	58252/90	EP	474756	SE 8901969
		US	5219087			
US	5878887	AU	73068/98	CA	2242448	EP 893359
		JP	11091822	NO	983265	
GB	2219284	NONE				
						END OF ANNEX

PATENT COOPERATION TREATY

PCT

INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference P17902PCAU	<div style="display: flex; justify-content: space-between;"> <div style="width: 30%;"> FOR FURTHER ACTION </div> <div style="width: 70%;"> see Notification of Transmittal of International Search Report (Form PCT/ISA/220) as well as, where applicable, item 5 below. </div> </div>	
International application No. PCT/AU01/00844	International filing date (<i>day/month/year</i>) 13 July 2001	(Earliest) Priority Date (<i>day/month/year</i>) 14 July 2000
Applicant WESTERN RESEARCH & DEVELOPMENT PTY LTD et al		

This international search report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

The international search report consists of a total of 4 sheets.

☒ It is also accompanied by a copy of each prior art document cited in this report.

1. Basis of the report

- a. With regard to the language, the international search was carried out on the basis of the international application in the language in which it was filed, unless otherwise indicated under this item.
- ☐ the international search was carried out on the basis of a translation of the international application furnished to this Authority (Rule 23.1(b)).
- b. With regard to any nucleotide and/or amino acid sequence disclosed in the international application, the international search was carried out on the basis of the sequence listing:

- ☐ contained in the international application in written form.
- ☐ filed together with the international application in computer readable form.
- ☐ furnished subsequently to this Authority in written form.
- ☐ furnished subsequently to this Authority in computer readable form.
- ☐ the statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.
- ☐ the statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished

2. ☐ Certain claims were found unsearchable (See Box I).

3. ☐ Unity of invention is lacking (See Box II).

4. With regard to the title, ☒ the text is approved as submitted by the applicant.
☐ the text has been established by this Authority to read as follows:

5. With regard to the abstract, ☒ the text is approved as submitted by the applicant
☐ the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.

6. The figure of the drawings to be published with the abstract is Figure No. 1

- ☐ as suggested by the applicant. ☐ None of the figures
- ☒ because the applicant failed to suggest a figure
- ☐ because this figure better characterizes the invention

INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU01/00844

A. CLASSIFICATION OF SUBJECT MATTER																					
Int. Cl. ⁷ : B65D 83/04, 55/02, 43/12 // B65D 101:00																					
According to International Patent Classification (IPC) or to both national classification and IPC																					
B. FIELDS SEARCHED																					
Minimum documentation searched (classification system followed by classification symbols)																					
Refer Electronic data base consulted below																					
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched																					
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)																					
DWPI IPC A61J 1/-, 3/-, 7/-, A45C 11/-, A47G 29/-, B65D 17/-, 43/-, 50/-, 51/-, 77/30, 83/04, 101/00 & keywords: TAMPER, FRANGIBLE, SEPARABLE, TAB, COVER and similar terms																					
DOCUMENTS CONSIDERED TO BE RELEVANT																					
Category*	Citation of document, with indication, where appropriate, of the relevant passages																				
X	US 4787526 A (PEHR) 29 November 1988 Column 11 lines 1-27 & See figures 31, 32																				
X	WO 90/14999 A (AKERLUND & RAUSING LICENS AB) 13 December 1990 See whole document																				
A	US 5878887 A (PARKER et al.) 9 March 1999 See whole document																				
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C <input checked="" type="checkbox"/> See patent family annex																					
Special categories of cited documents: <table border="0"> <tr> <td>"A"</td> <td>document defining the general state of the art which is not considered to be of particular relevance</td> <td>"T"</td> <td>later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</td> </tr> <tr> <td>"E"</td> <td>earlier application or patent but published on or after the international filing date</td> <td>"X"</td> <td>document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</td> </tr> <tr> <td>"L"</td> <td>document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</td> <td>"Y"</td> <td>document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</td> </tr> <tr> <td>"O"</td> <td>document referring to an oral disclosure, use, exhibition or other means</td> <td>"&"</td> <td>document member of the same patent family</td> </tr> <tr> <td>"P"</td> <td>document published prior to the international filing date but later than the priority date claimed</td> <td></td> <td></td> </tr> </table>		"A"	document defining the general state of the art which is not considered to be of particular relevance	"T"	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention	"E"	earlier application or patent but published on or after the international filing date	"X"	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone	"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y"	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art	"O"	document referring to an oral disclosure, use, exhibition or other means	"&"	document member of the same patent family	"P"	document published prior to the international filing date but later than the priority date claimed		
"A"	document defining the general state of the art which is not considered to be of particular relevance	"T"	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention																		
"E"	earlier application or patent but published on or after the international filing date	"X"	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone																		
"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y"	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art																		
"O"	document referring to an oral disclosure, use, exhibition or other means	"&"	document member of the same patent family																		
"P"	document published prior to the international filing date but later than the priority date claimed																				
Date of the actual completion of the international search	Date of mailing of the international search report - 5 NOV 2001																				
Name and mailing address of the ISA/AU AUSTRALIAN PATENT OFFICE PO BOX 200, WODEN ACT 2606, AUSTRALIA E-mail address: pct@ipaaustralia.gov.au Facsimile No. (02) 6285 3929	Authorized officer DEREK BUTLER Telephone No : (02) 6283 2347																				

INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU01/00844

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2219284 A (DRG (UK) LIMITED) 6 December 1989 See whole document	

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.
PCT/AU01/00844

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report				Patent Family Member			
US	4787526	AU	32806/89	CA	1316844	EP	401292
		WO	8908057	US	4925041	US	5013073
		US	5137260	US	4809874	US	4898073
		DE	3740691	EP	318681		
WO	9014999	AU	58252/90	EP	474756	SE	8901969
		US	5219087				
US	5878887	AU	73068/98	CA	2242448	EP	893359
		JP	11091822	NO	983265		
GB	2219284	NONE					
END OF ANNEX							

TENT COOPERATION TREATY

PCT

NOTIFICATION OF THE RECORDING
OF A CHANGE(PCT Rule 92bis.1 and
Administrative Instructions, Section 422)

From the INTERNATIONAL BUREAU

To:

WRAY & ASSOCIATES
P.O. Box 6292
Hay Street
East Perth, WA 6892
AUSTRALIEDate of mailing (day/month/year)
20 March 2002 (20.03.02)Applicant's or agent's file reference
105302International application No.
PCT/AU01/00844

IMPORTANT NOTIFICATION

International filing date (day/month/year)
13 July 2001 (13.07.01)

1. The following indications appeared on record concerning:

☐ the applicant☐ the inventor☒ the agent☐ the common representative

Name and Address

State of Nationality

State of Residence

Telephone No.

Facsimile No.

Teleprinter No.

2. The International Bureau hereby notifies the applicant that the following change has been recorded concerning:

☒ the person☐ the name☐ the address☐ the nationality☐ the residence

Name and Address

WRAY & ASSOCIATES
P.O. Box 6292
Hay Street
East Perth, WA 6892
Australia

State of Nationality

State of Residence

Telephone No.

Facsimile No.

Teleprinter No.

3. Further observations, if necessary:

An agent has been appointed, as indicated in Box 2. The agent's file reference should read as mentioned above: 105302.

4. A copy of this notification has been sent to:

☒ the receiving Office☐ the International Searching Authority☐ the International Preliminary Examining Authority☒ the designated Offices concerned☐ the elected Offices concerned☐ other:The International Bureau of WIPO
34, chemin des Colombettes
1211 Geneva 20, Switzerland

Facsimile No.: (41-22) 740.14.35

Authorized officer

Eric LESOT (Fax 338.87.40)

Telephone No.: (41-22) 338.83.38

004734288

PATENT COOPERATION TREATY

PCT

NOTIFICATION OF THE RECORDING
OF A CHANGE(PCT Rule 92bis.1 and
Administrative Instructions, Section 422)

From the INTERNATIONAL BUREAU

To:

WESTERN RESEARCH & DEVELOPMENT
LIMITED
Unit 4
50 Achievement Way
Wangara, W.A. 6065
AUSTRALIEDate of mailing (day/month/year)
26 February 2002 (26.02.02)Applicant's or agent's file reference
P17902PCAUInternational application No.
PCT/AU01/00844

IMPORTANT NOTIFICATION

International filing date (day/month/year)
13 July 2001 (13.07.01)

1. The following indications appeared on record concerning:

☒ the applicant ☐ the inventor ☐ the agent ☐ the common representative

Name and Address

WATERMARK PATENT & TRADEMARK ATTORNEYS
Level 21, Allendale Square
77 St Georges Terrace, Perth WA 6000

State of Nationality

AU

State of Residence

AU

Telephone No.

Facsimile No.

Teleprinter No.

2. The International Bureau hereby notifies the applicant that the following change has been recorded concerning:

☐ the person ☐ the name ☐ the address ☐ the nationality ☐ the residence

Name and Address

State of Nationality

AU

State of Residence

AU

Telephone No.

Facsimile No.

Teleprinter No.

3. Further observations, if necessary:

Watermark Patent & Trademark Attorneys advised to be no longer responsible attorneys for the above application.

4. A copy of this notification has been sent to:

☒ the receiving Office ☒ the designated Offices concerned
☐ the International Searching Authority ☐ the elected Offices concerned
☐ the International Preliminary Examining Authority ☐ other:The International Bureau of WIPO
34, chemin des Colombettes
1211 Geneva 20, Switzerland

Facsimile No.: (41-22) 740.14.35

Authorized officer

Paulette BOCCARD (Fax 338.87.40)

Telephone No.: (41-22) 338.83.38

004685966